


Print Method:	Thermal inkjet; Dye & Pigment ink
Print Resolution:	Up to 1200 x 4800 dpi
Print Speeds:	Draft Mode: 4.5" per second Normal Mode: 1.8" per second High Quality Mode: 0.8" per second
Print Head:	New print head with every cartridge change
Ink:	Single high capacity Cyan, Magenta, Yellow ink cartridge, process black
Colors:	16.7 million
Color Matching:	ICC color profiles for all Primera-supplied media. Ability to add custom ICC color profiles for other media types.
Print Width:	0.5" (13mm) to 8.25" (209mm)
Media Width:	1.5" (38mm) to 8.375" (212mm)
Media Types:	Roll-fed pressure-sensitive labels, roll-fed tags, fan-fold labels or tags
Media Sensing:	Moveable see-through sensor for die-cut labels; reflective sensor for labels and tags with black stripe; can use continuous and pre-printed labels and tags
Supply Roll:	6" (152mm) maximum diameter on 3" (76mm) core.
Ink Level Warning:	Calculates actual number of prints remaining based upon ink usage of graphics being printed (patent-pending)
Indicator Lights:	Power, Pause, Ink
Controls:	Pause, Load/Feed, Unload
Operating Systems:	Windows® 7/8x/10+ Mac OS X 10.9 or higher
Data Interface:	USB 2.0
Label Design Software:	Seagull Scientific Bartender® UltraLite Software version included; can also be used with most other popular label design & graphics programs
Electrical Rating:	12VDC, 5.0A
Power Requirements:	100-240VAC, 50/60 Hz, 60 watts
Certifications:	UL, UL-C, CE, FCC Class B

<p>California Prop 65:</p>	 <p>WARNING: Cancer and Reproductive Toxin .</p>
<p>Weight:</p>	<p>36.5 lbs. (16.6 kg)</p>
<p>Dimensions:</p>	<p>17.25"W x 9.1"H x 17.25"D (438mmW x 231mmH x 438mmD)</p>
<p>Included:</p>	<p>Bartender Ultralite software for Windows, non-perforated 4"X6" Tuffcoat™ Premium Gloss Inkjet Label Stock starter roll & ultra-high yield CMY dye ink cartridge.</p>