

Specifications LX600 Colour Label Printer

Print Method:	Thermal inkjet; Dye & Pigment ink
Print Resolution:	1200 x 1200 dpi native; up to 1200 x 4800 dpi
Print Speeds:	Up to 114.3 mm per second (4.5")
Ink:	Single high capacity CMY ink cartridge, process black
Colours:	16.7 million
Print Width:	13 mm (0.5") to 127 mm (5")
Media Width:	54 mm (2.125") to 133 mm
Media Types:	Roll-fed pressure-sensitive labels, roll-fed tags, fan-fold labels or tag
Media Sensing:	Moveable see-through sensor for die-cut labels, reflective sensor for labels and tags with black stripe; can use continuous and pre-printed labels and tags
Supply Roll:	152 mm (6") maximum diameter on 76Vmm (3") core
Cutter:	Built-in fully automatic pizza-wheel cutter
Operating Systems:	Windows® 7/8x/10+, Mac OS X 10.11 - macOS 10.15
Data Interface:	USB 2.0
Label Design Software:	BarTender UltraLite and NiceLabel Free 2019 DTM Version (Windows) Belight Swift Publisher 5 (Mac) Can also be used with most other popular label design & graphics programs
Electrical Rating:	12 V DC, 5.0 A
Power Requirements:	100 V-240 V AC, 50/60 Hz, 60 watts

Certifications:	UL, UL-C, CE, FCC Class A
Weight:	5.7 kg
Dimensions (WxHxD):	345 mm x 242 mm x 432 mm (13,6" x 9,5" x 17")
Manufacturer:	Primera Technology Inc.