

## Specifications LX610 Label Printer and Cutter

<b>Print Method:</b>	Thermal inkjet; Dye & Pigment ink
<b>Print Resolution:</b>	1200 x 1200 dpi native; up to 1200 x 4800 dpi
<b>Print / Cut Speeds:</b>	Pre-die cut media: Up to 114.3 mm per second (4.5"). Digital die-cut speeds are dependent upon the image being cut
<b>Print Head:</b>	New print head with every cartridge change
<b>Ink:</b>	Single high capacity CMY ink cartridge, process black
<b>Colours:</b>	16.7 million
<b>Print Width:</b>	Pre die-cut: 13 mm (0.5") to 127 mm (5") Die-cut: 13 mm (0.5") to 104 mm (4.1")
<b>Media Width:</b>	Pre die-cut: 54 mm (2.125") to 133 mm (5.25") Die-cut: 125 mm (4.75")
<b>Media Types:</b>	Roll-fed pressure-sensitive labels, roll-fed tags, fan-fold labels or tag
<b>Media Sensing:</b>	Moveable see-through sensor for die-cut labels; reflective sensor for labels and tags with black stripe; can use continuous and pre-printed labels and tags
<b>Supply Roll:</b>	152 mm (6") maximum diameter on 76 mm (3") core.
<b>Cutter:</b>	Built-in contour cutter + Built-in fully automatic pizza-wheel cutter
<b>Ink Level Warning:</b>	Calculates actual number of prints remaining based upon ink usage of graphics being printed (patent-pending)
<b>Indicator Lights:</b>	Power, Ink
<b>Controls:</b>	Pause, Feed, Unload
<b>Operating Systems:</b>	Windows® 7/8x/10+

<b>Data Interface:</b>	USB 2.0
<b>Label Design/Die-Cutting Software:</b>	Primera PTCreat <sup>™</sup> Pro Software included.
<b>Electrical Rating:</b>	12 V DC, 5.0 A
<b>Power Requirements:</b>	100-240 V AC, 50/60 Hz, 60 watts
<b>Certifications:</b>	UL, UL-C, CE, FCC Class A
<b>Weight:</b>	5.7 kg
<b>Dimensions:</b>	345 mm W x 242 mm H x 432 mm D (13.6"W x 9.5"H x 17"D)
<b>Included:</b>	PTCreat <sup>™</sup> Pro software for importing images and cutting a variety of label shapes. LX610e Pro also includes an ultra-high yield CMY dye ink cartridge, roll of DTM Paper Semi Gloss die-cutting label material.
<b>Manufacturer:</b>	Primera Technology, Inc.