

## Specifications CX86e colour tag printer

<b>Print Method:</b>	Full-colour electrophotographic with three separate LED print engines (CMY)
<b>Toner Cartridge:</b>	CMY three-colour toner cartridge
<b>Print Resolution:</b>	1200 x 1200 dpi
<b>Max. Print Speed:</b>	15.24 cm (6") per second; Idle mode to first label presented: 4 seconds
<b>Media Width:</b>	25 - 86 mm
<b>Media Length:</b>	53 - 551 mm
<b>Cutter:</b>	Built-in rotary cutter (cuttable media length 53 mm to 551 mm)
<b>Media Feed:</b>	External material feed via roll, continuous paper in zigzag folding or single sheet Sheet Feed: Paper cut into rectangles in the range of 25 mm to 86 mm width and 53 mm to 551 mm length
<b>Media Types:</b>	Self-adhesive label or tags, dry toner approved films (Use DTM Print certified Genuine Label Stock for a variety of approved dry toner materials)
<b>Media Sensing:</b>	Moveable transmission sensor for die-cut and through hole labels; Moveable reflective sensor for labels and tags with black stripe; can also use continuous and pre-printed labels and tags
<b>Cut Type Sensing:</b>	black mark (up/down) center holes side holes notch

	GAP defined length on continuous roll
<b>Display:</b>	Mono-LCD, 16 characters x 2 lines
<b>Memory:</b>	512 MB
<b>Data Interfaces:</b>	USB 2.0, Ethernet (100BASE-T/-T/10BASE-T), WLAN (optional), GPIO control port
<b>Design Software:</b>	NiceLabel Free 2019 DTM Edition included. Upgrade for data import and Variable Data Printing. Can also be used with most other popular label design and graphics software programs
<b>Printer Language:</b>	PCL6(PCL XL), PCL5c
<b>Command base embedded Barcode:</b>	PCL5c: 1D Barcode: 10 types, UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved 2of5, Code39, Code128, EAN/UCC-128, CODABAR, ZIP+4 POSTNET 2D Barcode: 2 types: PDF417, QR code (Model2 only) PCL6: N/A (Host based image data only)
<b>Windows Driver (PCL6):</b>	Windows 7, 8, 8.1, 10 Windows Server 2008, 2008 R2, 2012, 2012 R2, 2016
<b>Power Requirements:</b>	220 to 240 V AC, 50/60 Hz 110 V upon request
<b>Certifications:</b>	CE, GS, WEEE, RoHS2, REACH
<b>Weight:</b>	Approx. 9.5 kg
<b>Dimensions (WxHxD):</b>	198 x 380 x 195 mm (7.8" x 15" x 7.7")
<b>Manufacturer:</b>	DTM Print GmbH