

Specifications FX810e Foil Printer

Print Method:	Thermal transfer & direct thermal
Print Resolution:	300 dpi (12 dots/mm)
Max. Print Speed:	101.6 mm (4") per second
Max. Print Width:	219.5 mm (8.64")
Max. Print Length:	1016 mm (40")
Media Width:	108 - 255 mm (4" - 10")
Media Thickness:	0.05 - 0.25 mm (0.002" - 0.01")
Media Types:	Roll-fed continuous, die-cut or blackmark labels or tags; roll-fed tags with punched hole
Media Sensing:	Movable reflective sensor and central aligned transmissive sensors
Supply Media Roll:	38.1 - 76.2 mm (1.5-3") ID core with max. 254 mm (10") OD
Ribbon Width:	max. 220 mm (8.66") Recommendation: Choose the ribbon width depending on your layout. If your layout covers only 100 mm of the label, use a 100 mm wide ribbon roll.
Max. Ribbon Length:	300 m (981')
Supply Ribbon Roll:	25.4 mm (1") ID core with max. 68 mm (2.67") OD
Ribbon Types:	Wax, wax / resin, resin Recommended Ribbons: DTM Print certified thermal transfer ribbons in metallic colours (gold, silver, blue, red), spot colours and clear foil

Included:	Sturdy external passive label unwinder
Data Interface:	USB 2.0, Ethernet 10/100
Electrical:	100-240 V AC, 50/60 Hz 140 watts, standby 9,6 watts
Software (included):	NiceLabel Free 2019 DTM Edition
Operating Systems:	Windows 7/10
Printer Language:	EZPL, GEPL, GZPL
Indicator Lights:	Power/Standby, Feed/Pause/Cancel (Ready: Green, Error: Red)
Controls:	Power/Standby button with dual colour LED frame, Feed/Pause/Cancel dual-coloured button (Ready/Error), calibrate button at rear panel
Certifications:	CE, FCC Class B, RoHS
Weight:	11.7 kg
Dimensions:	432 mmW x 224 mmH x 221 mmD (16.9"W x 8.8"H x 8.7"D)
Note:	Colour label printers are not included in the price of the FX810e Foil Imprinting System.
Options:	FX810e FX810ec cutter module RW-7 External Label Rewinder RW-8 External Label Rewinder

Warranty	Three years warranty after product registration (read more at register.dtm-print.eu)
Manufacturer:	DTM Print GmbH